



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

1 Identification of substance

- **Product details**
- **Trade name:** ALT R350 Resin
- **Article number:** 158-351-010u
- **Application of the substance / the preparation** Coating
- **Manufacturer/Supplier:**
ALT Global, LLC
3 Edison Place,
Fairfield, NJ 07004 USA
Tel: 973-287-6158
Fax: 973-287-6159
- **Information department:** Tel.: 973-287-6158
- **Emergency information:**
For Chemical Emergency
Spill Leak Fire Exposure or Accident
Call CHEMTREC Day or Night

DOMESTIC NORTH AMERIKA 800-424-9300
INTERNATIONAL, CALL 703-527-3887 (collect calls accepted)

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

103-11-7	2-ethylhexyl acrylate	5-15%
2495-37-6	Benzylmethacrylat	5-15%
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol	<1%

3 Hazards identification

- **Hazard description:**



Irritant

- **Information pertaining to particular dangers for man and environment:**
The product has to be labelled due to the calculation procedure of international guidelines.
May cause sensitisation by skin contact.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 2

- **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0
FIRE 2 Fire = 2
REACTIVITY 2 Reactivity = 2

USA

(Contd. on page 2)



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

Trade name: ALT R350 Resin

(Contd. of page 1)

4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Take affected persons into fresh air and keep quiet.
Seek medical treatment in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Dispose contaminated material as waste according to item 13.
- **Additional information:** See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

USA



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

Trade name: **ALT R350 Resin**

(Contd. of page 2)

- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
Butyl rubber, BR
- **Not suitable are gloves made of the following materials:** Leather gloves
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing

9 Physical and chemical properties

· General Information

Form:	Fluid
Color:	Red
Odor:	Ester-like

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 101°C (214°F)

· **Flash point:** 82°C (180°F)

· **Ignition temperature:** 245°C (473°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Vapor pressure at 20°C (68°F):** 1.3 hPa (1 mm Hg)

· **Density at 20°C (68°F):** 1.83 g/cm³

(Contd. on page 4)

USA



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

Trade name: ALT R350 Resin

(Contd. of page 3)

- | | |
|--|-----------------------------|
| · Solubility in / Miscibility with Water: | <i>Insoluble.</i> |
| · Viscosity: | |
| Dynamic at 20°C (68°F): | <i>50 dPas</i> |
| · Solvent content: | |
| Organic solvents: | <i>0.2 %</i> |
| VOC content: | <i>4.3 g/l / 0.04 lb/gl</i> |
| · Solids content: | <i>81 %</i> |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Dangerous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
- **Dangerous products of decomposition:**
No dangerous decomposition products used according to specifications.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** *No irritant effect.*
- **on the eye:** *No irritating effect.*
- **Sensitization:** *Sensitization possible through skin contact.*
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

USA

(Contd. on page 5)



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

Trade name: ALT R350 Resin

(Contd. of page 4)

14 Transport information

- DOT regulations:
- Hazard class: -
- Land transport ADR/RID (cross-border):
- ADR/RID class: -
- Maritime transport IMDG:
- IMDG Class: -
- Marine pollutant: No
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: -

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

872-50-4 N-methyl-2-pyrrolidone

· TSCA (Toxic Substances Control Act):

21645-51-2 aluminium hydroxide

103-11-7 2-ethylhexyl acrylate

1309-37-1 diiron trioxide

8002-74-2 Paraffin waxes and Hydrocarbon waxes

80-62-6 methyl methacrylate

14808-60-7 Quartz (SiO₂)

38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

872-50-4 N-methyl-2-pyrrolidone

128-37-0 2,6-di-tert-butyl-p-cresol

108-65-6 2-methoxy-1-methylethyl acetate

7447-41-8 lithium chloride

Silan, dichlordimethyl-, Reaktionsprodukte mit Siliciumdioxid

123-86-4 n-butyl acetate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidone

· Cancerogenity categories

· EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E;NL

(Contd. on page 6)



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/04/2010

Reviewed on 12/15/2009

Trade name: ALT R350 Resin

(Contd. of page 5)

· IARC (International Agency for Research on Cancer)		
103-11-7	2-ethylhexyl acrylate	3
1309-37-1	diiron trioxide	3
80-62-6	methyl methacrylate	3
14808-60-7	Quartz (SiO ₂)	1
128-37-0	2,6-di-tert-butyl-p-cresol	3

· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K

· TLV (Threshold Limit Value established by ACGIH)		
1309-37-1	diiron trioxide	A4
80-62-6	methyl methacrylate	A4
14808-60-7	Quartz (SiO ₂)	A2
128-37-0	2,6-di-tert-butyl-p-cresol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	

· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Irritant

· **Hazard-determining components of labelling:**

2-ethylhexyl acrylate

Benzylmethacrylat

· **Risk phrases:**

May cause sensitisation by skin contact.

· **Safety phrases:**

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Avoid contact with skin and eyes.

Wear suitable gloves.

This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Division product safety

· **Contact:** Division product safety

· * **Data compared to the previous version altered.**