

# ALT Pigment 230 Additive



## Product Data Sheet

### Description

**ALT Pigment 230** is a color additive in an methyl-methacrylate base.

### Applications

**ALT Pigment 230** is mixed with ALT R230 unpigmented resin as a colorant.

### Colors

ALT Pigment 230 additive is available in a range of five standard colors as follows:

Grey	Dark Grey	Light Grey	Patina Green	Terracotta
------	-----------	------------	--------------	------------

ALT Pigment 230 is also available in an unlimited range of custom colors. Contact ALT Global Technical Department regarding specific colors and color matching capabilities.

### Packaging

ALT Pigment 230 is supplied in pre-measured 0.5 kg cans.

### Mixing Ratio

One pre-measured can of ALT Pigment 230 additive is required for each 9.5 kg drum of ALT R230 unpigmented resin.

### Coverage Rate

Refer to "ALT" resin product data sheet for coverage rate and recommendations for specific applications. Yields will vary depending upon system selected and the smoothness and absorbency of substrate.

### Storage

Always store in cool and dry location. Do not store in direct sunlight or in temperatures below 32°F(0°C) or above 77°F(25°C). Approximate shelf life is 6-months when left sealed, unmixed and with proper storage.

### Application Conditions

Refer to the "ALT" resin product data sheet for coverage rate and recommendations for specific applications.

### Mixing

Thoroughly mix the entire drum of resin for 2-3 minutes. Using a slow-speed mechanical agitator, slowly add the entire contents of ALT Pigment 230 to R230 unpigmented resin component while stirring; continue mixing for 2 to 5-minutes or until achieving a uniform streak-free color. Remix before each use, and prior to pouring off resin into a second container if batch mixing. Refer to "ALT" resin product data sheet for recommendations regarding catalyzing and application of resin.

### Working Times

Storage and working times are not affected by addition of this additive. Refer to the "ALT" resin product data sheet for specific working times.

### Safety Recommendations

Refer to product Material Safety Data Sheet (MSDS) prior to use or handling.

### Disposal

When mixed with resin, catalyzed and cured resin may be disposed of in standard landfills. ALT Pigment 230 additive should be treated as a hazardous material and must be handled as such, in accordance with local, state and federal regulations.

### Ordering Information

#### ALT Pigment 230 Additive

#388-###-105U

0.5 kg can

(Note: Substitute ### with appropriate ALT color code)

### DISCLAIMER

NO WARRANTY, EXPRESS OR IMPLIED, IS MADE IN THIS DOCUMENT. THE PRODUCT IS NOT CLAIMED TO BE MERCHANTABILITY OR FIT FOR ANY PARTICULAR PURPOSE. User and certified ALT Global system applicators determine suitability only. See individual ALT Global System product data sheets, MSDS sheets, guide specifications and details for complete information regarding the suitability, application and handling of ALT Global System products.